



## Intumescent Putty

**Trade Name: ASTROPUTTY**

### FEATURES

**Fire Putty tested to BS476: Part 20: 1987**

**EN1366-3**

**Up to 4 hours fire resistance**

**Non-setting**

**Easily removed and re-used**

**Fills hard-to-fire-protect irregular shapes**

**Certifire Approval**



### Description

An easy to use, non-setting intumescent compound, which is ideal for sealing around pipes and cables in walls and floors.

Can accommodate substantial movement of service penetrations and can be easily removed and re-used.

Its flexibility allows it to be used around complex and irregular shapes.

Offers excellent hot and cold smoke sealing properties and is not affected by fungal attack or moisture. Ideal for electrical, telecommunications and other such industries

The putty has been independently tested in accordance with BS476: Part 20: 1987 and EN1366-3 and can provide up to 4 hours fire resistance depending on depth and volume.

If you are buying putty to make putty pads for electrical socket boxes check our  
clean and full fire protection.

- quick,

### Availability

### PRODUCT CODE: AFIP

Astroflame Putty is red in colour and supplied in handy 1kg tubs.

### To Order & Specify

Please quote Quantity /Trade name /Product Code/ Weight.  
Typical wording- 12 / ASTROPUTTY / AFIP / 1kilo

### Fire Test Or Assessment Reports

## Health And Safety

The product does not present any known health hazards during or after installation. Normal good industrial and personal hygiene practices should be observed.

## Related Documents

As part of our policy of ongoing improvements, we reserve the right to modify, alter or change product specifications without giving notice. Product illustrations are representations only. All information contained in this document is provided for guidance only, and as ASTROFLAME FIRESEALS LTD has no control over the installation methods of the products, or of the prevailing site conditions, no warranties expressed or implied are intended to be given as to the actual performance of the products mentioned or referred to, and no liability whatsoever will be accepted for any loss, damage or injury arising from the use of the information given of products mentioned or referred to herein.

The above information to the best of our knowledge is true and accurate and based upon current test data and is supplied for your guidance only. Customers should satisfy themselves to the suitability of the product in its intended use and no guarantee is given or implied since the conditions of actual use are beyond our control. ASTROflame (Fireseals) Ltd, disclaim any liability for loss, damage or other expense arising from the use of information, data or products mentioned or referred to and reserve the right to change any details or specifications without notice.



Astroflame (Fire Seals) Ltd. Intumescent House  
Unit 8, The IO Centre, Stephenson Road, Segensworth  
FAREHAM, ENGLAND PO15 5RU

tel 0800 023 2482  
(01329 844500)

fax 0800 023 2483  
(01329 844600)

intl  
tel +44 1329 844500

fax +44 1329 844600

email